



“Make your machine more employable / profitable with the GMT 035 felling grapple”

FELLING GRAPPLE GMT 035

PRO



The felling grapple GMT 035 can be used by any machine that can handle a normal wood grapple. All this without having to do any technical modifications.

Because of the patented valve block, there is no need for extra hydraulic lines and / or electric cables.



The felling grapple GMT 035 has the following benefits:

- Enlarge the employability of your machine
- Fast cycle of operation, so usable near roads, railroads and in (public)parks
- Save up to 60% of man-hours
- Thanks to the saw cut there is no damage on the stem or tree trunk
- Remove or prune / shear / cut trees safely and efficiently



**“A safe and efficient way for trimming and removing trees”**

**FELLING GRAPPLE GMT 035**

**PRO**

**Technical details**

**Sizes**

Max opening grapple	850 mm
Max width with open grapple	950 mm
Min width with closed grapple	700 mm
Height at saw position	630 mm
Height at load position	500 mm
Weight	230 kg

**Hydraulics**

Minimum oil flow	40 ltr
Working pressure	180 / 250 bar

**Saw**

Length sawing blade	450 mm
Sawing chain	2 mm 404" 58 links
Max felling diameter	350 mm
Chain oil tank capacity	2 ltr
Sawmotor	10 cc



Gierkink Machine Techniek BV

Kapelweg 44

7134 RJ Vragender

the Netherlands

Tel +31 544 - 370315

Fax +31 544 - 370316

[www.gierkinkmt.nl](http://www.gierkinkmt.nl)

[info@gierkinkmt.nl](mailto:info@gierkinkmt.nl)